

RCW 46.61.355 Moving heavy equipment at railroad grade crossings

—Notice of intended crossing. (1) No person shall operate or move any crawler-type tractor, steam shovel, derrick, roller, or any equipment or structure having a normal operating speed of ten or less miles per hour or a vertical body or load clearance of less than one-half inch per foot of the distance between any two adjacent axles or in any event of less than nine inches, measured above the level surface of a roadway, upon or across any tracks at a railroad grade crossing without first complying with this section.

(2) Notice of any such intended crossing shall be given to the station agent of such railroad located nearest the intended crossing sufficiently in advance to allow such railroad a reasonable time to prescribe proper protection for such crossing.

(3) Before making any such crossing, the person operating or moving any such vehicle or equipment shall first stop the same not less than fifteen feet nor more than fifty feet from the nearest rail of such railroad and while so stopped shall listen and look in both directions along such track for any approaching train or other on-track equipment and for signals indicating the approach of a train or other on-track equipment, and shall not proceed until the crossing can be made safely.

(4) No such crossing shall be made when warning is given by automatic signal or crossing gates or a flagger or otherwise of the immediate approach of a railroad train or car or other on-track equipment. If a flagger is provided by the railroad, movement over the crossing shall be under the flagger's direction. [2017 c 87 s 3; 2000 c 239 s 7; 1975 c 62 s 32; 1965 ex.s. c 155 s 49.]

Captions not law—2000 c 239: See note following RCW 49.17.350.

Severability—1975 c 62: See note following RCW 36.75.010.