

WAC 246-231-106 Preliminary determinations. Before the first use of any packaging for the shipment of licensed material:

(1) The licensee shall ascertain that there are no cracks, pinholes, uncontrolled voids, or other defects that could significantly reduce the effectiveness of the packaging;

(2) Where the maximum normal operating pressure will exceed 35 kPa (five lbs/in²) gauge, the licensee shall test the containment system at an internal pressure at least 50 percent higher than the maximum normal operating pressure, to verify the capability of that system to maintain its structural integrity at that pressure;

(3) The licensee shall conspicuously and durably mark the packaging with its model number, serial number, gross weight, and a package identification number assigned by NRC. Before applying the model number, the licensee shall determine that the packaging has been fabricated in accordance with the design approved by NRC; and

(4) The licensee shall ascertain that the determinations in subsections (1) through (3) of this section have been made.

[Statutory Authority: RCW 70A.388.040 and 70A.388.110. WSR 23-21-056, § 246-231-106, filed 10/11/23, effective 11/11/23. Statutory Authority: RCW 70.98.050 and 70.98.110. WSR 17-01-034, § 246-231-106, filed 12/12/16, effective 1/12/17. Statutory Authority: RCW 70.98.050. WSR 14-09-017, § 246-231-106, filed 4/7/14, effective 5/8/14; WSR 08-09-093, § 246-231-106, filed 4/18/08, effective 5/19/08.]