

WAC 173-182-366 Transmission pipeline tank farms.

Time (hours)	Boom/Assessment	Minimum Oil Recovery Rate % of WCS volume per 24 hours	Minimum Storage in Barrels
1	A safety assessment of the spill by trained crew and appropriate air monitoring could have arrived		
2	2,000 feet of boom available at the spill source or downstream of the source could have arrived Alternatively, resources identified as a pipeline control point to keep oil from entering surface waters or penetrating into the ground could have arrived		
6	Additional 5,000 feet of boom available for containment, recovery or protection could have arrived Alternatively, additional resources identified as a pipeline control point to keep oil from entering surface waters or penetrating into the ground could have arrived	Capacity to recover the lesser of 10% of worst case spill volume or 8,000 barrels within 24-hour period could have arrived	1 times the EDRC
12	Additional 20,000 feet of boom to be used for containment, protection or recovery could have arrived	Capacity to recover the lesser of 15% of worst case spill volume or 36,000 barrels within 24-hour period could have arrived	1 times the EDRC
24	More boom as necessary for containment, recovery or protection	Capacity to recover the lesser of 20% of worst case spill volume or 48,000 barrels within 24-hour period could have arrived	2 times the EDRC
48	More boom as necessary for containment, recovery or protection	Capacity to recover the lesser of 25% of worst case spill volume or 60,000 barrels within 24-hour period could have arrived	More as necessary to not slow the response

[Statutory Authority: Chapter 90.56 RCW. WSR 16-21-046 (Order 15-08), § 173-182-366, filed 10/12/16, effective 11/12/16.]